

FLEET SPECIALS

EXPIRES JUNE 30, 2024



tifco industries

THE RIGHT PART, IN THE RIGHT PLACE, AT THE RIGHT TIME



FLEET SPECIALS

AIR / HAND TOOLS

PNEUMATIC IMPACT WRENCHES

1/2" SQUARE DRIVE

Professional Air Powered Impact Wrench 1/2" Square Drive Features a lightweight, durable composite housing and aluminum hammer case. Single-handed push-button forward/reverse operation and friction ring anvil for easy socket changing.

- Max Torque: 820 ft-lbs
- Length: 7-3/8" Weight: 4.2 lb
- Air Inlet: 1/4"
- Recommended hose size: 3/8"
- Average air consumption: 4 cfm

NEW



Part No.	Description
12226	1/2" Square Drive Air Powered Impact Wrench

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

PROFESSIONAL AIR POWERED WRENCH 3/4" SQUARE DRIVE

- Length: 9", Weight: 9.5 lb.
- Tool Air Inlet: 3/8", Rec Hose Size: 1/2"
- Torque Maximum: 1,100 ft. lb.
- Friction ring and thru-hole dual socket retention
- Durable steel hammer case, aluminum body holds up in heavy industrial use
- Average Air Consumption: 14-38 cfm

NEW



Part No.	Description
12248	3/4" Square Drive Air Powered Impact Wrench

IMPACT SOCKET SETS

- For use only on impact drivers
- Made of high alloy steel for greater strength and durability
- Socket wall dimensions are optimized for added strength while providing access to restricted fasteners

14 PIECE 6 POINT STANDARD SET - 3/4" DRIVE

SOCKETS

3/4"	1 1/16"	1 3/8"
13/16"	1 1/8"	1 7/16"
7/8"	1 3/16"	1 1/2"
15/16"	1 1/4"	1 5/8"
1"	1 5/16"	



Part No.	Description
11402	14 Piece 6 Point Standard 3/4-1 5/8



15 PIECE 6 POINT SET 1/2" DRIVE

CONTENTS

10mm	15mm	20mm
11mm	16mm	21mm
12mm	17mm	22mm
13mm	18mm	23mm
14mm	19mm	24mm



11373



11374

Part No.	Description
11373	15 Piece 6 Point Standard M10-24
11374	15 Piece 6 Point Deep M10-24



TORQUE WRENCHES

RATCHET HEAD, MICROMETER - ADJUSTABLE

- 24 tooth head design features push-button quick release
- Innovative linear ball bearing system eliminates friction for greater accuracy, produces audible "click" over entire torque range
- Detent locking ring allows easy setting of desired torque and prevents accidental change of setting while in use
- Knurled, grooved handle provides non-slip comfort grip
- Accuracy to $\pm 4\%$ clockwise (20 - 100% of full range)
- English scales primary, Newton meter secondary



Part No.	Description	Length
11988	3/8 drive, 10-100 ft./lb. (1/2 ft./lb. Incr.)	17.1"
11989	1/2 drive, 50-250 ft./lb. (1 ft./lb. Incr.)	20.5"



POWER TOOLS & ACCESSORIES

STRIP AWAY HUB AND STUD CLEANER KIT

Made from a tough synthetic fiber impregnated with silicon carbide abrasive grit. Safer alternative to wire bristle tools. Open coat design quickly cleans surfaces without damage or heat build-up.

- Removes rust and corrosion without excessive material removal or gouging
- Promotes proper wheel to hub torque
- Will not damage wheel stud threads
- Can also be used on most battery terminals



INCLUDES 10 DISCS

Part No.	Description/Contents
35240	1 1/2" x 5/8 Stud Cleaning Discs and (1) Backing Adapter
35241	2" x 5/8 Stud Cleaning Discs and (1) Backing Adapter

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

MBX REMOVE-ALL-SYSTEM

- Superior for removing vinyl, decals, D.O.T. tape on metal, OEM paint finishes, plate glass, aluminum, and fiberglass
- Removes multiple layers in one single step - no paint damage, no heat, no smearing, no vibration, no jumping
- New steady torque AC motor reduces time, effort and fatigue
- Notched eraser wheel - vents and cools surface: peels vinyl easily
- Wire belts remove paint, rust and corrosion in a fraction of the time used with conventional methods
- Cleans welding seams down to bare metal, removes oxidation on stainless steel, instant slag removal
- Full visibility to the working surface - the rotation of the wire belts create a chiseling motion, resulting in a sandblasted effect on the surface



Part No.	Description
5947	Air Tool w/3 Eraser Wheels, 5 Belts
5950	Replacement Eraser Wheels

RECIPROCATING AIR SAW KIT

- Professional quality, heavy duty construction and reliable performance
- Small body, short stroke, piston drive
- 10mm stroke is ideal for thin material
- Includes 5 ea: 14T, 18T, 24T blades and blow mold case

Specifications:

Speed: 10,000 strokes per minute

Length: 7 1/2"

Weight: 1 lb Air Inlet:

1/4" NPT Recommended Hose Size: 3/8"

ID Average Air Consumption: 7.6 CFM Max Air Pressure: 90 PSI



Part No.	Description
12240	Reciprocating Air Saw Kit

AIR SAW BLADES

- Bi-metal construction with hardened electron welded teeth for superior performance and long life
- Used for pneumatic machine cutting applications in auto repair and sheet metal
- Cuts most metals, fiberglass and plastics



5 PER PACK

Part No.	Teeth	Size
51546	14	3" x 1/2"
51547	18	3 5/8 x 1/2"
51548	24	3 5/8 x 1/2"

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

DRILL MOTOR MOUNTED ERASER WHEEL

- For quick and easy removal of decals, pinstripes, bumper stickers and reflective tapes from glass and OE painted surfaces
- Also removes tapes and glues from the back of mouldings
- 4" diameter, 1" width, 4000 max RPM
- Natural rubber construction
- Universal arbor - no special tools needed
- Use with electric or pneumatic drill



Part No.	Individual/Description
2531	Individual Eraser Wheel
2532	Box of 6 Eraser Wheels

FLEET SPECIALS

LED MINIBULBS

LED MINIATURE BULBS

















Instantly enhance the interior and exterior lighting applications of your vehicle with a modern, bright light for increased visibility by other motorists. Easy to install with a robust design and high-quality components.



NEW

- Delivers greater clarity with less power consumption and longer bulb life when compared to standard incandescent bulbs
- For some vehicles, installing a load equalizer may be required to eliminate hyper flash or dashboard error messages (Part No. **13799**)
- A direct replacement for the factory bulbs in your vehicle
- Provides full brightness instantly, giving drivers around you more time to react, compared to the slower light-up with incandescent bulbs

TWO BULBS PER PACKAGE

















	Part No.	Lamp No.	Base
	13755	168	Wedge
	13756	194White	Wedge
	13757	194 Red	Wedge
	13758	194 Amber	Wedge
	13759	194 Blue	Wedge
	13760*	211-2	Double End Cap
	13763	912	Wedge
	13764	921	Wedge
	13765	1156	S.C. Bay
	13766	1157	D.C. Index
	13767	2057	D.C. Index
	13770	3057	D.C. Wedge
	13772	3156	S.C. Wedge
	13774	3157	D.C. Wedge
	13775	3157A	D.C. Wedge
	13778	7443	D.C. Wedge

*13760 package contains one bulb



LED WEDGE MINIATURE BULB ASSORTMENT

85908


			
13755	13756	13757	13758
			
168	194 WHITE	194 RED	194 AMBER
			
13759	13760	13763	13764
			
194 BLUE	211-2	912	921

20 Pcs.



LED STOP TURN TAIL MINIATURE BULB ASSORTMENT

85909

			
13765	13766	13767	13770
			
1156	1157	2057	3057
			
13772	13774	13775	13778
			
3156	3157	3157 AMBER	7443

16 Pcs.

LOAD RESISTOR

Used to eliminate hyper flashing, error codes, and bulb out warnings. This most often occurs with turn signal applications in some vehicles, causing the bulb to blink must faster than normal or display a message on the dashboard after replacing an incandescent with an LED bulb.

- Easy to mount, attach load equalizer to a flat metal surface, then attach wires to those of socket with provided clips

Part No.	Description
13799	Set of 2 LED Bulb Load Resistors




NEW

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

FUSE HOLDERS

BLADE TYPE



ATO®

Part No.	Description	Wire Gauge	Max Amps	Picture
41934	In line with protective cap	14	20	B
41935	In line with protective cap	12	30	B
41937	6 pole fuse block side terminals	-	15	D
41938	Sealed fuse holder	12	30	E
41991	In Line	16	20	A
41992	In Line	12	30	A

Mini®

Part No.	Description	Wire Gauge	Max Amps	Picture
41930	In line with protective cap	14	20	B
41931	In line with protective cap	12	30	B
41932	Easy crimp	16 - 20	20	C

Maxi®

Part No.	Description	Max Amps	Picture
41939	In line with protective cap	60	B

J CASE

Part No.	Description	Max Amps	Picture
41928	Weatherproof Holder w/cover	50	F

MICRO

Part No.	Type	Wire Gauge	Max Amps	Picture
41917	Micro 2	12	30	G
41918	Micro 2	16	15	G
41916	Micro 3	14	20	G

LED INDICATING IN-LINE FUSE HOLDERS

- In-Line indicating fuse holder with waterproof cap
- PVC body with LED warning light that illuminates when fuse is opened/blown



Series	Part No.	Description (Max Amperage)
ATO	41990	12 AWG - 30 Amp
	42438	16 AWG - 15 Amp
Mini	41989	12 AWG - 30 Amp
	42441	16 AWG - 15 Amp
Micro 2	44229	12 AWG - 30 Amp
	44230	16 AWG - 15 Amp
Maxi	41999	6 AWG - 60 Amp



IN-LINE FUSEHOLDER ASSORTMENT

85751

41935 ATO 30 AMP	41934 ATO 20 AMP	41990 ATO 30 AMP LED	42438 ATO 15 AMP LED
41931 MINI 30 AMP	41930 MINI 20 AMP	41989 MINI 30 AMP LED	42441 MINI 15 AMP LED
41917 MICRO2 30 AMP	41918 MICRO2 15 AMP	44229 MICRO2 30 AMP LED	44230 MICRO2 15 AMP LED
41939 MAXI 60 AMP	41999 MAXI 60 AMP LED	41928 J-CASE 50 AMP	

30 Pcs.

LED INDICATING FUSE BLOCK

- Holds 6 ATO/ATC Fuses
- Each slot is numbered, and has an LED to indicate when the fuse has been blown
- Clear plastic cover prevents dust and water from entering the system
- 1/4" Quick connect tabs at each of the 6 slots
- #10-32 UNF post



Part No.	Description
3048	6 Slot LED Fuse Block

FUSE HOLDER & TAP ASSORTMENT			85671
41991 20 AMP ATO 14 GA HOLDER	41992 30 AMP ATO 12 GA HOLDER	41932 20 AMP MINI 16-20 GA HOLDER	
41934 20 AMP ATO 14 GA HOLDER	41935 30 AMP ATO 12 GA HOLDER	41939 100 AMP MAXI HOLDER	
41930 20 AMP MINI 14 GA HOLDER	41931 30 AMP MINI 12 GA HOLDER	41938 30 AMP ATO 12 GA HOLDER	
41928 J CASE FUSE HOLDER	41997 MINI FUSE TAP	41998 ATO FUSE TAP	

46 Pcs.

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

FLEET SPECIALS

FLEET CONNECTORS

4-WAY FLAT TO 7-WAY TRAILER ADAPTER


- 4-Way flat male and hardwire connectors with 7-Way RV blade female socket
- 4' long 4-Way connector



Part No.	Description
2912	4-Way/7-Way Trailer Adapter

5-WAY TO 7-WAY TRAILER ADAPTER


- 7-Way RV blade male plug with 5-Way flat female
- Designed for marine type trailers equipped with surge brakes
- Adapts vehicle 7-Way RV blade to trailer 5-Way flat



Part No.	Description
2918	7-Way/5-Way Trailer Adapter

4-WAY FLAT EXTENSION CONNECTOR

- 4 feet long, 18 Ga. Wire
- Used to connect your vehicle to your trailer when your trailer frame is too long



Part No.	Description
42203	4-Way Trailer Extension

4-WAY 5' WIRING KIT

- Molded plastic polarized plugs
- 16 Ga. color coded wires
- Vehicle female 48" leads
- Trailer male 12" leads
- Includes 3 splice connectors



Part No.	Description
42193	4-Way Trailer Connector Kit

4-WAY 24' WIRING KIT

- Molded plastic polarized plugs
- 16 Ga. color coded wires
- Vehicle female 4' leads and 18" ground lead
- Trailer male 20' leads and 18" ground lead
- Includes 6 splice connectors



Part No.	Description
42194	4-Way Trailer Kit

4-POLE MALE AND FEMALE CONNECTOR KIT

- Chrome plated metal male and female 4-Pole ends
- Mounting bracket and hardware
- 4', 16 Ga. color coded wires
- 3 splice connectors



Part No.	Description
42195	4-Pole Trailer Kit

6-POLE MALE AND FEMALE CONNECTOR KIT

- Die cast chrome plated metal plug
- Molded plastic socket and boot
- Mounting bracket and hardware
- 4', 16 Ga. color coded wires
- 5 splice connectors



Part No.	Description
42196	6-Pole Trailer Kit

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

TRAILER CABLES & ACCESSORIES

7-WAY TRAILER CABLES

COILED CABLE WITH CABLE GUARD

- All cables have abrasion resistant duraflex jackets, 12" leads
- 12507 features 40" pigtail for easier handling
- Flexible in temperatures to -85°F (-65°C)
- 12504 & 12505 Cable use Weatherseal sealant lined boot for strain relief and corrosion resistance



Part No.	Length	Gauges
12591	15'	6/14 - 1/12
12505 *	15'	4-12, 2-10, 1-8
12507 *	15'	4-12, 2-10, 1-8 w/ 40" Pigtail
12501	12'	4-12, 2-10, 1-8, w/red, blue air
12509	15'	4-12, 2-10, 1-8, w/red, blue air

*SAE J2394 for ABS systems

7 POLE PLUGS

- Exclusive spring clip release
- Single set screw cable clamp
- Integral cable clamp
- Replaceable interior



DIE CAST METAL PLUG

- Corrosion resistant die cast construction

Part No.	Description
2937	Plug with Cable Projector



HEAVY DUTY

- Long life "Spring Grip" contacts for reliable connections
- Heavy-duty, corrosion resistant die cast construction
- Increased electrical efficiency, easier uncoupling

COLE HERSEE

Part No.	Description
2936	Plug with Cable Projector



TRAILER CONNECTOR KITS

MASTER TRAILER CLEANER SET

CLEAN ANY TRAILER CONNECTOR

For 4, 5, 6, 7 Flat/Spade and 7 Round Trailer Connectors. The unique patented design allows for precise removal of corrosion from both male and female pins, while maintaining proper pin dimensions. The Trailer Connector Cleaner Master Set is also great for cleaning butt and bullet type connectors found on most tail and side marker assemblies. Includes custom-sized swabs for removing debris and applying the supplied DeoxIT® contact enhancer solution.

- Maintain continuity and prevent circuit failure
- Clean and re-size trailer pins
- Remove corrosion from connectors
- Extend harness life
- Use as a pin wear gauge
- **Additional Applications:** Bullet, Butt and Blade Terminals

Contents:


4 and 5 Round Pin
6 Round Pin
7 Flat (Spade) Pin
7 Round Pin
Swab-Eez® 8mm and 5mm Head
DeoxIT® Contact Cleaner



Part No.	Description
3081	Master Trailer Cleaner Set

7 POLE SOCKETS

- Zinc die-cast housing for durability
- Elongated holes for mounting adaptability
- Stainless steel hinge pin and spring for long-life
- Full-opening lid
- Meets SAE J560 specifications
- Reduce exposure to contaminants & moisture



Part No.	Description
2943	7-way, Split Pin

⚠ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

FLEET SPECIALS

CARGO CONTROL

QUICKLOADER - AUTO-RETRACTING

- Heavy duty, spring loaded coil automatically retracts and stores webbing resulting in no loose webbing flapping around
- Stronger locking mechanism
- Longer handle is easier to ratchet
- Extended release keeps from pinching fingers
- Longer webbing for more versatility



Part No.	Size	Working Load Limit (lbs)	Breaking Strength (lbs)	Ends
35096	1.5" x 15 Ft.	1,500	4,500	D-rings & Double J-hooks
35097	2" x 27 Ft.	3,333	10,000	Double J-hooks
35098	2" x 27 Ft.	3,333	10,000	Flat Hooks

SELF-TENSIONING RATCHET STRAP

- Automatically tightens the webbing if there is a load shift
- Ratchet features 2 large coil springs that in the case of a load shift, the ratchet will re-tighten taking up a maximum of 2" of webbing
- Double J-Hooks
- Chromate finished hardware protects against damaging your cargo
- D.O.T. compliant printed web



Part No.	Size	Max Vehicle Weight
35118	1.5" x 15'	1,333 lbs.
35120	2" x 27'	3,300 lbs.

KINETIC RECOVERY TOW ROPE

- Made from 100% nylon
- Reinforced pull loops adds strength where it's needed most
- Coated to increase abrasion resistance
- Breathable and reusable storage bag for proper storage

**CREATES A SLINGSHOT EFFECT
TO HELP RECOVER YOUR
VEHICLE**



Part No.	Size	Max Vehicle Weight
35622	7/8" x 20'	11,010 lbs.
35623	1.25" x 30'	22,100 lbs.

CARGO STRAPS W/EDGE GUARD RATCHET TIE DOWNS

- 100% Nylon, flat steel hooks, 18" fixed end, plated ratchet
- Premium *edge-guard* strap resists fraying

- Work load limit: 2,500 Lbs.
- Tensile strength: 10,000 Lbs.



2" x 27 FT.

Part No.	Description
35167	Ratchet and 2" x 27 Ft. w/Flathook
35168	Ratchet and 2" x 27 Ft. w/J hook
35132	Replacement Strap w/Flathook

4" WINCH STRAPS

- Work load limit: 5000 Lbs.
- Tensile strength: 20,000 Lbs.



4" x 30 FT.

Part No.	Description
35163	Ratchet and 4" x 30 Ft. Strap w/Flathook
35166	Replacement Strap w/Flat Hook
35164	Replacement Strap w/Chain Hook
35159	Replacement Ratchet Handle Only

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

AUXILLARY LIGHTING

LED LICENSE LIGHT

A 1.5" round LED License Light. It snaps into place for easy installation and comes with chrome stainless bezel. It is DOT FMVSS108 compliant for License Plates utilizing a 2-lamp system.

- 12.8V DC, 40mA
- 1.5" Dia. x 1.7"
- 1.25" mounting hole
- Two 7" blunt cut wire leads
- 4 LEDs
- DOT SAE - J587

Maxxima

NEW



Part No.	Description
3383	LED License Light

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

LICENSE LIGHT AND BRACKET

Contains 2-LED sealed license light, gray bracket and a gasket

- White in color
- 12V, 0.027mA
- Hard-wired connection with 180" male bullets
- 3.438" x 2.688" x 2.313"

NEW



Part No.	Description
3382	2-LED License Light

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

LED DOME LIGHT

- Low profile design, hard wired
- Polycarbonate lens and housing
- On-off switch
- 3 flange mounting holes

Maxxima



3353

Part No.	Lumens
3353	900

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

LED INTERIOR COMPARTMENT LIGHT

- Equipped with Extreme-Flux LEDs for superior cool white light output and low amp draw
- Surface mount design with four mounting screws for easy installation
- Epoxy coated sealed electronics that are refrigeration safe
- Snap-on polycarbonate lens, refrigeration and moisture safe
- Rated at 100,000 hours
- 2 wire leads
- Operating voltage: 12.8 VDC
- Dimensions: 5.8" wide x 2.9" high x 0.7" deep

Maxxima



Part No.	Lumens	Diodes
3357	200	14
3358	530	18

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

ANTI-SLIP PRODUCTS

ANTI-SLIP TRACTION TAPE

- Made of wear resistant mineral coating on adhesive
- Easy to install - adhesive backed - requires minimum maintenance
- Continues to provide a positive non-skid grip even when exposed to water, grease and oil
- Reduces the chance of injury from slips and falls
- Can be cut to desired length and width and are ideal for stairs, walkways, and ramps
- **Part Nos. 4489 and 7159** are pre-cut strips
- Ideal for stairs, walkways, and ramps



4488



4489/7159

Part No.	Width	Length	Color
4484	4"	60 ft.	Black/Yellow
4485	2"		Black
4486	4"		Black
4487	6"		Black
4488	2"		Black/Yellow
4490	2"	24"	Clear
4489	6"		Black (50 Strips)
7159	6"		Black (10 Strips)

HIGH-TRACTION TAPE

- Durable construction stands up to oil, diesel fuel, grease and mud in most extreme environments
- 46-grit silicon carbide surface ensures consistent, long-lasting, slip-resistance
- NFSl - National Flooring Safety Institute certified for "high traction"



60 FOOT ROLLS - BLACK

Part No.	Width
7160	2"
7161	4"
7162	6"

TRACTION AEROSOL NO-SLIP EPOXY COATING

TIFCO Traction is a slip resistant clear epoxy coating that cures to a hard, flat, textured finish. This product is the most cost effective way to treat small areas. Traction is designed for interior and exterior use on concrete, steel, wood, fiberglass, aluminum, tile, etc. For interior and exterior use on steps, ramps, load docks, or anywhere water or other slippery conditions exist. It applies easily and cures quickly. It contains a synthetic grit with no sharp edges.



Part No.	Description
7602	Case of 12 (16 oz. Cans)
9902	1/2 Case of 6 (16 oz. Cans)

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

FLEET SPECIALS

LED LIGHTING

LED DOUBLE FACE SQUARE

PEDESTAL TURN LIGHT

- Polycarbonate lens; red and amber
- Single post; 3 wire leads
- Sealed moisture corrosion proof electronics
- 21 red LEDs and 21 amber LEDs
- Dimensions(W x H x D): 4.50" x 4.75" x 2.25"



3552



3553

Part No.	Description
3552	Passenger
3553	Driver

LED COMBINATION STOP TURN TAIL LIGHTS

- Smoothly illuminated outer band that surrounds a center LED array that remains unlit during standard taillight operation
- Dual-function out ring brightens and the central LED array lights only during stop and turn functions
- 21 Diodes
- Grommet mount
- Polycarbonate lens and housing
- Connection: PL-3



Part No.	Description
3555	4" Round STT



Part No.	Description
3556	6" Oval STT

LED CLEARANCE LIGHT 3/4" MINI-ROUND CLEAR P2PC

- Sealed electronics, grommet included
- Hard wired with male bullet connector
- Polycarbonate lens and housing



3348



3309

NEW



3349

Part No.	Description
3348	3 Diode Red Light
3349	3 Diode Yellow Light
3309	3 Diode Clear Light

Optronics


100,000 HOUR RATED LIFE

- High impact polycarbonate lens and housing are sonically welded
- Uses standard 3-pin connector (Part No. 3422)

Maxxima



3151



3152



3155



3157

Part No.	Description	Plug No.	Grommet No.
3140	6 Diode Red 4"	3422	3494
3150	32 Diode Red 4"	3422	3494
3151	9 Diode Red 4"	3422	3494
3152	9 Diode Amber 4"	3422	3494
3154	42 Diode Red Oval	3422	3426
3155	9 Diode Red Oval	3422	3426
3141	6 Diode Red Oval	3422	3426
3157	15 Diode Amber Oval	3422	3426

6" LED DRY-FIT OVAL LIGHTS

The DryFit Series allows for easy drop-in replacement on vehicles equipped with OEM style harness like the Truck-Lite *Fit N' Forge* connector. All 12.8 volt, Dry-Fit light feature sealed, moisture proof electronics, superior lens optics and plate brass connectors.

Maxxima

- Integrated Dry-Fit connector mates with **Part No. 3432**

PARK/REAR TURN LIGHT


- Dimensions: 6.4" W x 2.2" H x 1.7" D
- Mounting: Grommet

3363



6" OVAL PARK/REAR TURN

Part No.	Color	Diodes
3366	Amber	9
3365	Red	6
3363	Red	9



3366

BACK-UP LIGHT

- LEDs: 18
- Dimensions: 6.4" W x 2.0" H x 1.7" D
- Mounting: 6" Grommet



Part No.	Description
3319	6" Oval Back-Up Light

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

EMERGENCY LIGHTING

LED DUAL EMERGENCY WARNING LIGHT

- Amber/White color
- 27 selectable flash patterns with a built-in flasher module
- Strong aluminum housing with 2-hole mounting gasket
- Four, 8" blunt cut wire leads
- 6 LEDs
- Dual 12/24V DC
- 1.7" Dia. x .9"

NEW



Part No.	Description
3470	Dual Color Emergency Light

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

LED STROBE LIGHT


- 4 extremely powerful LEDs, state-of-the-art driving technology and cutting-edge optics to produce the brightest surface-mount LED lamp on the market.
- 8 User-selectable flash-patterns, including Single Flash (steady burn), Quad Flash, Staggered Flash
- Meets SAE Class 1 requirements, 12/24V
- Height: 1.25 inches
- Depth: 3/8 inches
- Width: 4.5 inches
- Rated Current: 0.5 amps max at 12/8V



Part No.	Description
3482	LED Strobe Light
3483	Grille Mounting Bracket - Flat
3484	Grille Mounting Bracket - 90° Angle

LED SURFACE MOUNT WARNING LIGHTS

- SAE Class 1 and California Title 13 Certified
- Features 3 high powered LED's w/aerodynamic 360° wide angle lensing for maximum output
- Fully encapsulated circuitry, weatherproof, aluminum housing
- 12/24VDC; 4 selectable flash patterns
- Two heads can be connected for a synchronized flash pattern
- 5" L x 2 3/8" W x 1" Tall



Part No.	Description
3476	Low Profile - Flush Mount

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

CLASS 1

- High powered LEDs offer 360° visibility
- 4.6" at base, 3.5" at lens
- 12/24V DC, 1.2A maximum
- 72 Quad-Flashes per minute
- Sonic-welded polycarbonate housing
- 2714 features 60lb. pull magnet, 15' straight cord and plug
- Warranty: 5 Years



Part No.	Description
2713	Amber Permanent Mount LED Beacon
2714	Amber Magnetic Mount LED Beacon

LED BEACON SAFETY LIGHTS

FIREBOLT® CLASS 2


- Features an innovative LED emitter that produces a superior warning signal to promote work zone safety
- The amber LED technology in allows for a minimal amp draw while meeting Class 2 standards.
- Designed to meet the demands of a variety of work zones including snow plows, forklifts, utility trucks and construction vehicles
- 14 selectable flash patterns
- Made of a shatterproof polycarbonate dome and base, includes an O-ring to help keep out moisture
- Approvals: SAE J845 Class 2
- 12/24V, Amp Draw: 0.5A @ 12 VDC; 0.25A @ 24 VDC
- Dimensions: 5.1" diameter base x 3.6" high
- 5 year warranty



Part No.	Description
2700	Permanent Mount
2702	Magnetic Mount

ECONOMY LOW-PROFILE LED MINI-LIGHT BARS

- 12/24V light weight, high impact LED display
- 2.75" low profile dome, 13.25" wide
- 1.2 Amps at 12.8V, preprogrammed flash patterns
- Warranty: 5 Years



Part No.	Description
2707	Permanent Mount
2708	Magnetic Mount

FLEET SPECIALS

MIRRORS

WEST COAST STYLE

- Heavy duty, two channel construction, 5/16" stud mounting
- Universal design to fit all O.E.M. brackets
- Heated unit has 60" wire for 12 volt systems



Part No.	Size	Description
3375	6 1/2 x 16	Anodized Aluminum
3377	7 x 16	Heated - Stainless Steel
3378	7 x 16	Heated - S/S w/marker lamp

CONVEX

- Provides wide angle vision on trucks, buses, and equipment
- 5/16" adjustable female ball stud and bolt
- L-bracket included, universal center mounting stud
- Heated mirror #3580 has self regulating element and 16 gauge, 77" power lead



Part No.	Size	Description
3583	5"	Black Enamel
3578	6"	Stainless Steel
3584	8 1/2	Stainless Steel
2673	8 1/2	Black Enamel
3580	8 1/2	Heated - Stainless Steel

OFFSET STUD MOUNTING

Part No.	Size	Description
2670	8 1/2	Stainless Steel



OVER-DOOR CONVEX - RECTANGLE

- Universal mounting (hole slots 5/16" x 9/16")
- O.E.M. replacement, fits either side of vehicle



Part No.	Size	Description
3577	4" x 8"	Stainless Steel

LIGHTS

RECTANGULAR AMBER CLEARANCE MARKER LIGHTS P2PC WITH WHITE GROUND LIGHT

- Dual color, dual function, clearance marker lamp and ground illumination light
- Improve driver safety by lighting up the ground at night around the tractor and/or trailer
- The white auxiliary light is designed for stationary applications, and not recommended for moving vehicles
- The tree-wire connection allows a dedicated circuit and switch to activate the ground light
- Light features a polycarbonate lens and housing
- 70 Lumen white light directed downward
- LEDs: 16 (10 Amber + 6 White)
- Voltage: 12.8VDC
- Dimensions: 4" W x 2" H x 1" D
- Connector: 3 5" leads, 2 .180 Bullets, 1 Ring



NEW

Part No.	Description
3126	LED Clearance Light with Ground Light

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

6" OVAL SIDE TURN WITH REFLECTOR

Optronics

- Dry-Fit connection allows for easy drop-in replacement on vehicles equipped with OEM style harnesses
- 10 LEDs
- Connector - weather tight, 3-pin (Part No. 3461)
- Amperage Draw: .201A Turn, .054 Marker
- Dimensions (W x H x D): 7.875" x 3.313" x 2.500"
- 6" Flange - Recess
- Polycarbonate Lens & Housing
- Color: Amber



NEW

Part No.	Description
3554	6" Oval Amber Turn

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

AUTOMOTIVE HORN

- High-frequency vibrator horn for industrial/commercial applications
- Mounting bracket included
- 2 terminals with 12V DC
- 134 db at 4 meters



NEW

Part No.	Description
2480	Automotive Horn

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

SAFETY PRODUCTS

ANSI CLASS 2 - MESH FABRIC

- ANSI 107 Class 2 Hi-visibility polyester-mesh fabric vest
- 2 inch silver reflective tape

Zipper Closure Style has 2 lower internal pockets, 2 upper chest pockets and 4 pen pockets

Hook & Loop Closure Style has 1 internal lower pocket and 1 external chest pocket



ZIPPER CLOSURE

Part No.	Size
6894	Large
6895	X-Large
6896	2X-Large
6897	3X-Large
6898	4X-Large
6899	5X-Large

HOOK & LOOP CLOSURE

Part No.	Size
6580	Large
6581	X-Large
6582	2X-Large

CLASS 2 TWO TONE SAFETY VEST

- Zipper front closure.
- 2" wide reflective stripes on 4" contrast trim.
- 6 pockets total: 1 clear ID flap pocket (4"x4"), 1 two tier chest pocket with pen/tool slots, 2 lower flap gusset pockets, 2 inside tablet pockets with load bearing straps
- 2 mic tabs
- 100% Polyester, mesh upper body, solid lower body, full mesh back
- ANSI/ISEA 107-2020 | Class 2



Part No.	Description
6583	Large
6584	X-Large
6585	2X-Large
6586	3X-Large

PROGRIP™ TURBO DRIVER'S GLOVE

- Top grain leather for maximum comfort and strength
- Weltd seams on middle fingers to allow for narrower fingertips
- Applications: maintenance operations, construction, masonry, agriculture, transportation, and electrical contractors

PROGRIP



GOATSKIN

- Strongest, lightest weight leather
- Impressive breathability
- Unbelievable flexibility and tactility



Size	Part No. Pair	Part No. Dozen
Medium	6635	906635
Large	6636	906636
X-Large	6637	906637
2X-Large	6640	906640

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

COLD WEATHER INSULATED CLASS 3

- 100% waterproof, heavy duty 300D polyester canvas outer fabric
- Lined hand warmer pockets, adjustable hood
- 32" 3-in-1 parka has 260 gram heavyweight zip-out removable fleece liner
- Hook & loop wrist adjusters
- Zippered chest pocket and clear I.D. chest pocket



REMOVABLE LINER

Part No.	Size
6714	Medium
6715	Large
6716	X-Large
6717	2X-Large
6718	3X-Large

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

CLASS 3 WATERPROOF FLEECE-LINED PARKA JACKET

- 300D Oxford with PU Coated Shell
- All sealed seals, concealed hood and zip closure with snap storm flap
- 1 inner chest pocket, 2 lower-slant pockets, cell phone pocket; 2 pen holder pockets on sleeve
- Elasticized wrist cuffs and waist band
- Mic holders cuffs
- ANSI/ISEA 107-2015 Class 3



Part No.	Size
21169	Large
21170	X-Large
21171	2X-Large
21172	3X-Large
21173	4X-Large

PROGRIP™ BOOST SYNTHETIC DRIVER'S GLOVE

- Fully synthetic leather drivers glove
- Man made material is incredibly consistent, the same high quality for every pair
- Synthetic material has performance characteristics similar to pigskin

PROGRIP



Size	Part No. Pair	Part No. Dozen
Large	2791	902791
X-Large	2792	902792

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

FLEET SPECIALS

SWITCHES

TOGGLE - 25 AMPS AT 12 VOLTS D.C.

- Plastic housing with plated steel cap
- Stem and mounting hardware are nickel plated brass
- Nickel plated brass handles
- Mounting stem 15/32"-32 thd., 15/32" long, with keyway
- Fits panels up thru 1/4" thick
- Silver contacts for dependable electrical operation



TOGGLE SWITCH ASSORTMENT

85753

2957 SPST ON-OFF	3010 SPST ON-OFF	3012 SPST OFF-MOMENTARY ON	3013 SPST ON-OFF
3058 SPST ON-OFF	3054 SPST ON-OFF	3055 SPST OFF-MOMENTARY ON	2958 SPDT ON-OFF-ON
3011 SPDT ON-OFF-ON	3015 SPDT ON-OFF-MOMENTARY ON	2951 SPDT MOM. ON-OFF-MOM. ON	3056 SPDT ON-OFF-ON
2955 DPST ON-OFF	2954 DPDT ON-OFF-ON	3057 DPDT ON-OFF-ON	2949 RUBBER SEAL

17 Pcs.

ROUND ROCKER SWITCHES

- Housing: Black Nylon 66
- 25/32" (20mm) Mounting Hole
- 20A 14V DC
- Single Pole, Single Throw
- Off-On
- .187" Blade Terminal



ROCKER AND TOGGLE SWITCH ASSORTMENT

85846

3035 SPST OFF-ON	3038 SPST OFF-MOM. ON	3041 SPDT ON-OFF-ON	3043 SPDT MOM. ON-OFF-MOM. ON
3075 SPST OFF-ON AMBER	3076 SPST OFF-ON GREEN	3077 SPST OFF-ON RED	3078 SPST OFF-ON BLUE
3051 SPST RECTANGULAR OFF-ON	3052 SPDT RECTANGULAR ON-OFF-ON	3053 SPST RECTANGULAR OFF-ON RED	3016 SPST OFF-ON
3017 SPDT ON-ON	3018 SPDT ON-OFF-ON	3024 SPST OFF-ON AMBER	3025 SPST OFF-ON GREEN

32 Pcs.

RELAYS

- Typical applications: lighting control, starting, horn, heating and cooling
- General purpose, automotive relays fit many vehicles
- Standard ISO footprint 4 Terminal SPST and changeover 5 terminal SPDT
- Diode suppressor is more efficient at dissipating EMF
- Mounting tabs available on most relays

HEAVY DUTY

- Heavy duty: 40A at 12V DC; High power: 70A at 12V DC

Part No.	Form	Amp	Voltage	Suppressor
2601	SPST	40	12	None
2602	SPST	40	12	Resistor
2603	SPST	40	12	Diode
2607	SPDT	40	12	None
2608	SPDT	40	12	Resistor
2604	SPDT	40	12	Diode
2609	SPST	20	24	None
2610	SPST	20	24	Resistor
2625	SPDT	20	24	None



SPST

HIGH POWER

- Mounting tab is not available on Part Nos. 2629, 2632, 2633

Part No.	Form	Amp	Voltage	Suppressor
2611	SPST	70	12	None
2634	SPST	70	12	Diode
2635	SPDT	70	12	None
2613	SPDT	70	12	Resistor
2629	SPDT	100	12	None
2632	SPDT	100	12	Resistor
2633	SPDT	100	12	Diode



SPDT

ELECTRO-MECHANICAL FLASHERS

- Exceeds SAE J-590A specifications

12 VOLT

Part No.	Mfg. No.	Application	Term	Lamps
2616	EL12	Auto/Light Truck	2	1-10
2617	EL13	Auto/Light Truck	3	1-10
3407	852/5X	Truck/Trailer	2	1-8



3407



2616

RELAY, FLASHER & PIGTAIL ASSORTMENT

85088

2601	2602	2607	2608
2609	2610	2611	2613
2616	2617	3409	3411
27750	27751	552 FLASHER 27752	27713
4 PIN 6.5" RELAY PIGTAIL		14GA 19" RELAY PIGTAIL	5 TERMINAL RELAY WIRING HARNESS

21 Pcs.

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

BATTERY TERMINALS & ACCESSORIES

BATTERY CONNECTORS & LUGS (CRIMP TYPE)

- Battery lugs and connectors are color-coded by battery cable size to assure proper crimping
- Each lug and connector has crimping marks to assure a proper location of compressions
- Connectors provide high pull out values and are easy to insulate with heat shrinkable insulators



1/0 GA. HEAVY DUTY BATTERY CONNECTOR ASSORTMENT

85918

44816 1/0 GA. NEGATIVE STRAIGHT TERMINAL	44806 1/0 GA. POSITIVE STRAIGHT TERMINAL	44836 1/0 GA. NEGATIVE FLAG TERMINAL
44826 1/0 GA. POSITIVE FLAG TERMINAL	44866 1/0 GA. x 3/8" BOLT BATTERY LUG	44846 1/0 GA. x 1/2" BOLT BATTERY LUG
44876 1/0 GA. x 3/8" BOLT STUD SIDE LOCKING LUG	44784 1/0 x 3/8 BOLT MAGNALUG	44785 1/0 x 1/2 BOLT MAGNALUG
42452 5/16-18 x 1 1/2 BATTERY BOLT W/NUT	4172 UNIVERSAL S/S STUD TOP BATTERY NUT	44591 RED HEAT SHRINK TUBING 44597 - BLACK #6-1/0 GA. x 6"

73 Pcs.



2/0 GA. HEAVY DUTY BATTERY CONNECTOR ASSORTMENT

85919

44817 2/0 GA. NEG. STARIGHT	44807 2/0 GA. POS. STRAIGHT	44837 2/0 GA. NEG. FLAG
44827 2/0 GA. POS. FLAG	44867 2/0 GA. X 3/8" LUG	44847 2/0 GA. X 1/2" LUG
44877 2/0 GA. X 3/8" LUG	44789 2/0 X 3/8 MAGNALUG	44790 2/0 X 1/2 MAGNALUG
42452 5/16-18 x 1 1/2 BOLT W/NUT	4172 UNIVERSAL S/S STOD NUT	44592 #1-4/0 GA. X 6" RED HEAT SHRINK 44598 - BLACK

73 Pcs.

BATTERY CRIMP KIT

- Contains crimp tool (Part No. 44599) cable stripper (Part No. 44594) heat shrink tubing and assorted battery terminals and lugs




Part No.	Pieces	Size/Description
44994	40	2/0 Battery Crimp Kit
44995	40	1/0 Battery Crimp Kit

RED KOTE

BATTERY SEALANT & METAL PROTECTOR

RED KOTE Protectant sealant provides a visible red coating that contains high quality corrosion inhibitors for long lasting protection. High performance formula is self healing and will not crack, flake or run. Protects metal against salt - water spray, rain, humidity and other types of moisture. It will not affect paint or primed surfaces and offers excellent corrosion resistance to metal parts and machinery.

- Prolongs battery life, increases performance
- Will not crack or flake
- Resists corrosion, salt spray, moisture
- Also used on cables, vehicles, carts, machinery, boats and metal parts
- 20 fl. oz., 15 oz. net wt.



Part No.	Description
7614	Case of 12 Aerosol Cans
9954	1/2 Case of 6 Aerosol Cans



BATTERY CABLE SLICER

- Cuts up to 250 MCM cable
- 22" handles for easier cutting
- Blades made of 1075 carbon steel, hardened for long life, can be resharpened



Part No.	Description
44593	Battery Cable Slicer



BATTERY CRIMP TOOLS

- Heavy duty handles with cushion grips
- Multiple settings using simple, 2-finger adjustment knob
- No dies means 30% smaller head width and lower crimp pressure required
- Unlike hex crimp, triangle crimp applies even pressure on connectors with no pinch corners
- Triangle shaped crimp for solid copper crimp of connector and cable
- Crimps all major brands of battery terminals, copper lugs, and splices
- For SAE/AWG gauge cable



Part No.	Size/Description	Length
44615	8 Ga - 1/0	16"
44617	8 Ga - 250 MCM	25"




WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

FLEET SPECIALS

LARGE BORE TIRE VALVE PRODUCTS

LARGE BORE SWIVEL VALVE

- Can be used with a tubeless spud or a screw in spud
- 3 1/8 inches long
- 80 degree bend angle



NEW

Part No.	Description
48737	Large Bore Swivel Valve

LARGE BORE SWIVEL FOOT GAUGE

- Made out of Nickel-plated brass
- Nylon slide bar
- Easy to read
- Calibrated 10 - 150 in 2lb. units
- Swivels 360 degrees for hard to reach valves



NEW

Part No.	Description
48724	Large Bore Swivel Foot Gauge

LARGE BORE LOCK-ON AIR CHUCK (LONG)

- Locks on valve when cocked on threads
- Has greater air flow and seat cannot be blown out if seal fails
- Also for use with Super Large Bore
- 1/4" NPT Female thread



NEW

Part No.	Description
48726	Large Bore Lock-On Air Chuck (Long)

LARGE BORE CLIP-ON AIR CHUCK

- Locks on valve when sleeve is pushed forward and releases when sleeve is pulled back
- Has greater air flow and seat cannot be blown out if seal fails
- 1/4" NPT Female thread
- 1.75" long



NEW

Part No.	Description
48727	Large Bore Clip-On Air Chuck

TIRE INFLATION

TIRE INFLATOR/DEFLATOR GAUGE

- Hose fitting is 1/4" NPT and accepts all standard 1/4" NPT air chucks
- Inflates tires up to 25% faster than other inflator gauges
- Manufactured with high quality materials, and replaceable parts for easy maintenance
- Traditional Analog or back lighted Digital gauge faces provides an easy reading of PSI



48545



48544

Part No.	Description
48544	Analog 10-160 PSI
48545	Digital 10-150 PSI

DUAL HEAD AIR CHUCKS

- Extended reach and length makes inflating inner dual wheel easy
- Dual-Head and Straight Foot styles available
- Maximum pressure 150 PSI
- 1/4" Female NPT end



48596



48597



48784



48788

Part No.	Description	Length
48596	Dual Angled Head - Extended Reach	12 1/4"
48597	Dual Head Straight - Extended Reach	12 3/4"
48784	Dual Angled Head	6 1/2"
48788	Dual Head Straight Foot	6 3/4"

INNER DUAL TIRE VALVE EXTENSION

- Standard bore, maximum 150 PSI
- Effective length 7"
- 2 per card
- Clamp with attached bolt allows for easy connection to truck rim when mounting valve extension




Part No.	Description	PSI
48776	Inner Dual Tire Valve Extension Set	150

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

AIR BRAKE PRODUCTS

RETRACTABLE AIRCOILS - NYLON

- 1/2" Male pipe thread on each end
- Sets consist of one blue and one red hose




Part No.	Description
12494	12' Standard
12495	15' Standard
12496 *	15' w/40" Pigtail
12497 *	15' w/40" Pigtail & Brass Handle

*40 inch pigtail for greater wear protection and easier handling

HEAVY DUTY POLYURETHANE

- Abrasion resistant polyurethane cover
- Abrasion resistant polyurethane; Flexgrip Handles on trailer pigtail, superior durability, coil memory and kink resistance
- Cold weather resistant to -75°F, excellent chemical resistance
- Part #12500 is bonded together to prevent tangles
- Swivel fittings at tractor end for quick installation



Part No.	Description
12499	15' Standard Heavy Duty w/Brass Handles
12500	15' Bonded Heavy Duty w/Brass Handles

CAB BLOWER KIT

- 1/8" tee, 1/4" recoil tubing
- Mounts under seat, blowgun included
- Taps into existing airline for convenient access



Part No.	Description
35145	72" with Spring Guards

SUPREME ALUMINUM GLADHANDS

- Top-of-the-line gladhands with tough powder coating that improves wear and corrosion resistance
- Vividly colored to provide improved identification of service and emergency lines
- Stainless steel clamp and wear plate eliminates corrosion of critical mating surfaces
- Stainless steel filter restricts dirt particles from entering the system
- Polyurethane seals are oil and chemical resistant and provide improved sealing and service life



Part No.	Description
35111	Package of 1 Emergency - Red & 1 Service - Blue
35113	Emergency - Red
35114	Service - Blue

FLEX-GRIPS GLAD HAND GRIPS

- Unique rubberized gladhand grips that may be used on rubber hose assemblies or air coils
- Protect hose/tubing during gladhand connection
- Allow gradual bend restriction during tight turns
- Packed in a field install set



Part No.	Description
35101	Red & Blue Gladhand Grip Pack

LONG HANDLED GLADHAND COUPLINGS

- Easier coupling and uncoupling with added leverage
- Ergonomic grip reduces the change of kinking airlines and extends their life
- Integrated hex at the base provides for easy installation
- Eliminates the potential leak point between a gladhand and grip
- Anodized aluminum features superior corrosion and salt spray resistance for harsh winter conditions



Part No.	Description
35099	Package of 1 Emergency - Red & 1 Service - Blue
35092	Service - Blue
35093	Emergency - Red


WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

FLEET SPECIALS

WELL NUTS

The Well Nut Threaded Insert is a flanged neoprene bushing with a brass machine nut molded into one end. Tightening a conventional machine screw thread in the brass nut causes the insert to expand, making a secure fastening.

- Fastens in blind holes, removable
- Helps seal out ambient moisture
- Dampens vibration and shock, muffles noise
- Helps prevent galvanic corrosion
- Ideal for metal-to-plastic and other mixed material fastenings
- Installs with conventional tools
- Commonly used for luggage and roof racks, attaching outdoor brackets and signs, license plates and automotive brackets.



Part No.	Thread	Grip Range	Hole Size
29859	6-32	0.015-0.165"	5/16
29861	8-32	0.015-0.172"	5/16
29862	10-24	0.030-0.227"	3/8
29863	10-32	0.15-1-0.192"	3/8
29864	10-32	0.035-0.232"	3/8
29865	10-32	0.312-0.643"	3/8
29894	1/4-20	0.015-0.111"	1/2
29866	1/4-20	0.031-0.187"	1/2
29896	1/4-20	0.187-0.343"	1/2
29895	1/4-20	0.250-0.457"	1/2
29867	5/16-18	0.015-0.187"	5/8
29879	5/16-18	0.15-0.374"	5/8
29883	3/8-16	0.015-0.437"	3/4
29891	M5-0.8	0.015-0.192"	3/8
29897	M6-1.0	0.031-0.187"	1/2
29898	M8-1.25	0.015-0.156"	5/8



WELL NUT & SCREW ASSORTMENT

85639

29861 8-32 X .560 .015 - .172 GRIP RANGE FITS 5/16" HOLE	29865 10-32 X 1.051 .312 - .643 GRIP RANGE FITS 3/8" HOLE	29895 1/4-20 X 1.051 .250 - .457 GRIP RANGE FITS 1/2" HOLE	29891 M5-8 X 14.07 .015 - .192 GRIP RANGE FITS 3/8" HOLE	17645 10-24 X 1" STAINLESS STEEL MACHINE SCREW 17635	16130 3/8-16 X 1 1/4" STAINLESS STEEL CAP SCREW 70632
29862 10-24 X .767 .030 - .227 GRIP RANGE FITS 3/8" HOLE	29894 1/4-20 X .630 .015 - .111 GRIP RANGE FITS 1/2" HOLE	29867 5/16-18 X .725 .015 - .156 GRIP RANGE FITS 1/2" HOLE	29897 M6-1.0 X 21.06 .031 - .187 GRIP RANGE FITS 5/8" HOLE	17635 10-32 X 1" STAINLESS STEEL MACHINE SCREW 16010	70632 M5-0.80 X 20 STAINLESS STEEL CAP SCREW 70643
29863 10-32 X .554 .015 - .152 GRIP RANGE FITS 3/8" HOLE	29894 1/4-20 X .801 .187 - .343 GRIP RANGE FITS 1/2" HOLE	29867 5/16-18 X 1.098 .15 - .374 GRIP RANGE FITS 5/8" HOLE	29897 M8-1.25 X 18.41 .015 - .156 GRIP RANGE FITS 5/8" HOLE	17623 1/4-20 X 1 1/4" STAINLESS STEEL CAP SCREW 16070	70657 M6-1.00 X 25 STAINLESS STEEL CAP SCREW 70657
29864 10-32 X .665 .035 - .232 GRIP RANGE FITS 3/8" HOLE	29866 1/4-20 X .829 .031 - .187 GRIP RANGE FITS 1/2" HOLE	29867 3/8-16 X 1.062 .015 - .437 GRIP RANGE FITS 3/4" HOLE	29897 8-32 X 3/4" STAINLESS STEEL MACHINE SCREW 17623	16070 5/16-18 X 1 1/4" STAINLESS STEEL CAP SCREW 16070	70657 M8-1.25 X 25 STAINLESS STEEL CAP SCREW 70657

330 Pcs.


JACK NUTS

The Jack Nut Threaded Insert is a blind fastener designed for use in thin, soft, or brittle materials. When tightened, the body collapses to form legs which grip the inside of the mounting surface, leaving a permanent, reusable threaded insert.

- Fastens in blind holes, Raintite features watertight seal ring
- Won't distort or deform soft plastics or thin sheet metals
- Securely fastens despite burrs or uneven substrate
- Suitable for wide grip range
- Helps prevent galvanic corrosion



Part No.	Thread	Finish	Grip Range	Hole Size
29900	10-24	Zinc	0.015-0.187"	.385-.400"
29901	1/4-20	Zinc	0.015-0.187"	.434-.450"
29902	1/4-20	Zinc	0.187-0.375"	.434-.450"
29860	1/4-20	Zinc w/Sealer	0.015-0.187"	.434-.450"
29904	M6-1.0	Zinc w/Sealer	0.015-0.187"	.434-.450"



JACK NUT INSTALLATION TOOL

- Designed to effortlessly install Jack Nuts
- Size range: 6-32 - 1/4-20, M4-M6
- Install threaded fastener into Jack Nut, insert into tool slot, place into pre-drilled hole and squeeze until set
- Tighten the fastener to complete installation



Part No.	Description
29905	Jack Nut Tool

WELL NUT & JACK NUT ASSORTMENT

85645

29861 8-32 X .750 .750 HEAD DIA. FITS 5/16" HOLE	29865 10-32 X 1.051 .562 HEAD DIA. FITS 3/8" HOLE	29895 1/4-20 X 1.051 .635 HEAD DIA. FITS 1/2" HOLE	29891 M5-8 X 14.07 12.70 HEAD DIA. FITS 3/8" HOLE	29901 1/4-20 X .731 438 BODY DIA. .015 - .187 GRIP RANGE	29905 JACK NUT INSTALLATION TOOL
29862 10-24 X .580 .562 HEAD DIA. FITS 3/8" HOLE	29894 1/4-20 X .630 .630 HEAD DIA. FITS 1/2" HOLE	29867 5/16-18 X .725 .875 HEAD DIA. FITS 1/2" HOLE	29897 M6-1.0 X .829 750 HEAD DIA. FITS 5/8" HOLE	29902 1/4-20 X .819 438 BODY DIA. .187 - .375 GRIP RANGE	
29863 10-32 X .554 500 HEAD DIA. FITS 3/8" HOLE	29896 1/4-20 X .635 .635 HEAD DIA. FITS 1/2" HOLE	29879 5/16-18 X 1.098 .846 HEAD DIA. FITS 5/8" HOLE	29898 M8-1.25 X 18.41 22.22 HEAD DIA. FITS 5/8" HOLE	29860 1/4-20 X .731 438 BODY DIA. .015 - .187 GRIP RANGE	
29864 10-32 X .665 .562 HEAD DIA. FITS 3/8" HOLE	29866 1/4-20 X .829 .750 HEAD DIA. FITS 1/2" HOLE	29883 3/8-16 X 1.062 1.125 HEAD DIA. FITS 3/4" HOLE	29900 10-24 X .716 .382 BODY DIA. .015 - .187 GRIP RANGE	29904 M6-1.0 X .760 438 BODY DIA. .015 - .187 GRIP RANGE	

171 Pcs.

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

SELF PIERCING RIVETS


- Mechanically join two or more layers of material without the need for a predrilled hole
- Joining of sheet materials is achieved by inserting a rivet and cold-forming an interlock with cycle times similar to spot welding
- Just clamp the sheets and press the self-piercing rivet through the top layers of material to upset the rivet in the bottom layer

Part No.	Diameter	Overall Length
30079	3.35mm	3.5mm
30080		4mm
30081		5mm
30082		6mm
30083	5.30mm	4mm
30084		5mm
30085		6mm
30086		6.5mm
30087		7mm
30088		7.5mm
30089		8mm
30090		9mm
30091		10mm
30092		12mm



SELF PIERCING RIVET TOOLS

- Use with a 3/4" or 19mm socket on a 1/2" impact wrench
- Heavy duty construction that uses a grade 8 bolt



Part No.	Description
30093	Extraction Tool
30094	Installation Tool

SELF PIERCING RIVET ASSORTMENT 85310				
30079 Self Piercing Rivet 3.35mm x 3.5mm	30080 Self Piercing Rivet 3.35mm x 4mm	30081 Self Piercing Rivet 3.35mm x 5mm	30082 Self Piercing Rivet 3.35mm x 6mm	30083 Self Piercing Rivet 5.3mm x 4mm
30084 Self Piercing Rivet 5.3mm x 5mm	30085 Self Piercing Rivet 5.3mm x 6mm	30086 Self Piercing Rivet 5.3mm x 6.5mm	30087 Self Piercing Rivet 5.3mm x 7mm	30088 Self Piercing Rivet 5.3mm x 7.5mm
30089 Self Piercing Rivet 5.3mm x 8mm	30090 Self Piercing Rivet 5.3mm x 9mm	30091 Self Piercing Rivet 5.3mm x 10 mm	30092 Self Piercing Rivet 5.3mm x 12mm	
30070 Pop Rivet 1/4" Dia. Grip: 0.060 - 0.138"	30071 Pop Rivet 1/4" Dia. Grip: 0.110 - 0.189"	30072 Pop Rivet 1/4" Dia. Grip: 0.189 - 0.238"	30073 Pop Rivet 1/4" Dia. Grip: 0.268 - 0.346"	

390 Pcs.

AUTOMOTIVE RIVETS



FORD AUTOMOTIVE RIVET ASSORTMENT

85682

28410 1/8" Dia. 1/8" - 3/16" Grip	28676 1/8" Dia. 1/16" - 1/8" Grip	29808 1/8" Dia. 3/16" - 1/4" Grip	29817 3/16" Dia. 1/32" - 1/4" Grip	29800 3/16" Dia. 3/8" - 1/2" Grip
28414 3/16" Dia. 3/64" - 13/64" Grip	28006 1/4" Dia. 1/8" - 1/4" Grip	28007 1/4" Dia. 3/32" - 1/8" Grip	28101 1/4" Dia. 3/32" - 9/64" Grip	28326 1/4" Dia. 1/8" - 5/16" Grip
28327 1/4" Dia. 3/16" - 3/8" Grip	28328 1/4" Dia. 1/32" - 7/32" Grip	28400 1/4" Dia. 1/8" - 21/64" Grip	28407 1/4" Dia. 25/64" - 21/32" Grip	29801 1/4" Dia. 1/8" - 1/4" Grip
29804 1/4" Dia. 1/32" - 9/64" Grip	29805 1/4" Dia. 33/64" - 19/32" Grip	29806 1/4" Dia. 11/16" - 3/4" Grip	29807 1/4" Dia. 1/32" - 7/32" Grip	29818 1/4" Dia. 1/32" - 7/32" Grip

325 Pcs.



GM AUTOMOTIVE RIVET ASSORTMENT

85683

28409 5/32" Dia. 3/64" - 1/4" Grip	29815 5/32" Dia. 3/64" - 1/4" Grip		
29807 1/4" Dia. 1/32" - 7/32" Grip	29804 1/4" Dia. 1/32" - 9/64" Grip	28324 1/4" Dia. 1/16" - 5/32" Grip	28323 1/4" Dia. 1/16" - 1/4" Grip
29819 1/4" Dia. 7/64" - 11/64" Grip	28008 1/4" Dia. 9/64" - 3/16" Grip	28005 1/4" Dia. 33/64" - 19/32" Grip	29806 1/4" Dia. 11/16" - 3/4" Grip
28414 3/16" Dia. 3/64" - 13/64" Grip	28402 3/16" Dia. 3/64" - 11/32" Grip	28814 3/16" Dia. 5/64" - 23/64" Grip	28085 3/16" Dia. 3/64" - 23/64" Grip

285 Pcs.



PEEL-TYPE SPECIALTY RIVET ASSORTMENT

85742

28327 1/4" Dia. 3/16" - 3/8" Grip	28328 1/4" Dia. 1/32" - 7/32" Grip	28400 1/4" Dia. 1/4" - 21/64" Grip	28407 1/4" Dia. 25/64" - 21/32" Grip
29804 1/4" Dia. 1/32" - 9/64" Grip	29805 1/4" Dia. 33/64" - 19/32" Grip	29806 1/4" Dia. 11/16" - 3/4" Grip	29807 1/4" Dia. 1/32" - 7/32" Grip
29817 3/16" Dia. 1/32" - 1/4" Grip	29818 1/4" Dia. 1/32" - 7/32" Grip	28414 3/16" Dia. 3/64" - 13/64" Grip	29819 1/4" Dia. 7/64" - 11/64" Grip
28007 1/4" Dia. .090" - .125" Grip	28008 1/4" Dia. 9/64" - 3/16" Grip	28101 1/4" Dia. 3/32" - 9/64" Grip	28006 3/4" Dia. 1/8" - 1/4" Grip

205 Pcs.

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

FLEET SPECIALS

AUTOMOTIVE CLIPS & RETAINERS

PANEL CLIP PLIERS

- Features a unique two-step tip
- Provides better support under the clip head than conventional panel clip pliers
- Added support allows removal of panel clips without damaging the clip
- Double cushion-grip handle



NEW



Part No.	Description
29907	9" Panel Clip Pliers

FORD AUTOMOTIVE RETAINER ASSORTMENT 85178

28493 5mm x 10mm Stem 5mm x 15mm Head	28248 5/32" Stem Dia. Weatherstrip Retainer	28530 Fits 6.5mm Hole Size 7.05 - 9.5mm Panel Range	28533 Fits 8.5mm Hole Size 4.5 - 7.0mm Panel Range	28089 1/4" x 35mm Stem 18mm Head Dia.
28482 5/16" x 13/16" Stem 3/4" Head Dia.	28375 5/16" x 1" Stem 3/4" Head Dia.	28376 11/32" x 3/4" Stem 3/4" Head Dia.	28257 11mm x 28mm Stem 22mm Head Dia.	28449 8mm x 20mm Stem 25mm Head Dia.
28318 1/4" x 25/32" Stem 1" Head Dia.	29706 1/4" x 1 1/2" Stem 1" Head Dia.	28043 5/16" x 7/8" Stem 1" Head Dia.	28258 5/16" x 1 1/2" Stem 1" Head Dia.	28443 5/16" x 11/16" Stem 1 1/4" Head Dia.
28542 5/16" x 1" Stem 1 3/8" Head Dia.	29919 5/8" Stem Length 9/32" Head Dia.	29917 3/8" Stem Dia. 1 3/16" Head Dia.	28545 Fits 5/16" Hole Size 9/16" x 2" Head Size	29761 3/8" x 3/4" Stem 1 3/4" Head Dia.

260 Pcs.

GM CHRISTMAS TREE RETAINER ASSORTMENT 85184

28034 5/16" x 11/16" Stem 15/16" Head Dia.	28035 5/16" x 1 1/8" Stem 15/16" Head Dia.	28036 7/16" x 1 7/16" Stem 1" Head Dia.	28042 5/16" x 1 3/8" Stem 3/4" Head Dia.	28044 14mm Stem DIA. 18mm Head Dia.
28047 3/16" x 1/2" Stem 3/4" Head Dia.	28054 5/16" x 11/16" Stem 5/8" Head Dia.	28055 11/32" x 11/16" Stem 9/16" Head Dia.	28056 5/16" x 11/16" Stem 15/16" Head Dia.	28057 9/32" x 1/2" Stem 3/4" Head Dia.
28059 7/16" x 13/16" Stem 1" Head Dia.	28062 5/16" x 3/4" Stem 3/4" Head Dia.	28372 9/32" x 1 3/32" Stem 1 1/32" Head Dia.	28430 5/16" x 3/4" Stem 1/2" Head Dia.	29910 5/16" x 3/4" Stem 7/8" Head Dia.
29924 5/16" x 3/4" Stem 2" Head Dia.	29965 5/16" x 5/8" Stem 11/16" Head Dia.	29966 5/16" x 13/16" Stem 11/16" Head Dia.	29976 9/32" x 3/4" Stem 1/2" Head Dia.	30008 5/16" x 3/4" Stem Door Panel Clip

230 Pcs.

GM ROCKER PANEL MOULDING CLIP ASSORTMENT 84742				
29877 9MM HOLE SIZE STEM LENGTH: 15MM	29878 9MM HOLE SIZE STEM LENGTH: 14MM	28188 9MM HOLE SIZE STEM LENGTH: 14MM	29881 9MM HOLE SIZE STEM LENGTH: 15MM	29882 9MM HOLE SIZE STEM LENGTH: 11MM
28520 M9.5 HOLE SIZE OVERALL LENGTH: 23MM	29885 3/8" HOLE SIZE TOP HEAD: 9/16" X 13/16"	29886 10MM HOLE SIZE TOP HEAD: 12MM X 20MM	29887 7/16" HOLE SIZE STEM LENGTH: 9/16"	29888 7/16" HOLE SIZE STEM LENGTH: 9/16"
29889 7/16" HOLE SIZE STEM LENGTH: 9/16"	28540 7/16" HOLE SIZE STEM LENGTH: 9/32"	29892 7/16" HOLE SIZE STEM LENGTH: 9/16"	28480 7/16" HOLE SIZE STEM LENGTH: 9/16"	28481 7/16" HOLE SIZE STEM LENGTH: 9/16"
29912 7MM HOLE SIZE STEM LENGTH: 13MM	28102 7/16" HOLE SIZE STEM LENGTH: 1 1/4"	29913 5/16" HOLE SIZE STEM LENGTH: 9/16"	28094 5/16" HOLE SIZE STEM LENGTH: 9/16"	29932 10MM HOLE SIZE STEM LENGTH: 15MM

200 Pcs.

UNIVERSAL PLASTIC SHIELD RETAINER ASSORTMENT 85681

29701 1/8" x 3/8" Stem 7/32" Head Dia.	28313 3/16" x 7/16" Stem 23/64" Head Dia.	28048 7/32" x 3/8" Stem 3/8" Head Dia.	29702 7/32" x 5/8" Stem 3/8" Head Dia.	28317 6mm x 12mm Stem 10mm Head Dia.	28314 7/32" x 23/64" Stem 13/32" Head Dia.
28315 3/16" x 5/8" Stem 7/16" Head Dia.	29705 1/4" x 1/4" Stem 29/64" Head Dia.	29976 9/32" x 3/4" Stem 1/2" Head Dia.	29708 21/64" x 39/64" Stem 1/2" Head Dia.	28259 3/8" x 3/4" Stem 5/8" Head Dia.	29704 1/4" x 49/64" Stem 41/64" Head Dia.
29964 5/16" x 5/8" Stem 11/16" Head Dia.	29966 5/16" x 13/16" Stem 11/16" Head Dia.	29703 3/16" x 11/16" Stem 3/4" Head Dia.	29707 5/16" x 1 1/16" Stem 3/4" Head Dia.	28042 5/16" x 1 3/8" Stem 3/4" Head Dia.	28319 11/32" x 7/8" Stem 3/4" Head Dia.
28257 11mm x 28mm Stem 22mm Head Dia.	28268 Fits 1/4" Hole 20mm Stem Length	28318 1/4" x 25/32" Stem 1" Head Dia.	29706 1/4" x 1 1/2" Stem 1" Head Dia.	28316 19/64" x 1 1/16" Stem 1" Head Dia.	28059 7/16" x 13/16" Stem 1" Head Dia.

420 Pcs.

GM CHRISTMAS TREE RETAINER ASSORTMENT 85074

29701 1/8" x 3/8" Stem 7/32" Head Dia.	28280 5.5mm x 11mm Stem 13mm Head	29964 5/16" x 5/8" Stem 11/16" Head Dia.	29707 5/16" x 1 1/16" Stem 3/4" Head Dia.	28064 7/16" x 13/16" Stem 7/8" Head Dia.
29925 5/32" x 3/8" Stem 13/32" Head Dia.	28670 5/16" x 3/4" Stem 9/16" Head Dia.	28197 9.5mm x 14mm Stem 18mm Head Dia.	28319 11/32" x 7/8" Stem 3/4" Head Dia.	28372 9/32" x 1 3/32" Stem 1 1/32" Head Dia.
29705 1/4" x 1/4" Stem 29/64" Head Dia.	28666 7/32" x 3/4" Stem 19/32" Head Dia.	28375 5/16" x 1" Stem 3/4" Head Dia.	28458 11/32" x 1 3/16" Stem 3/4" Head Dia.	28091 Dodge Ram Trim Panel Retainer
28500 2mm x 12mm Stem 12mm Head Dia.	29699 5/16" x 1/2" Stem 11/16" Head Dia.	29909 5/16" x 1" Stem 3/4" Head Dia.	28667 5/16" x 15/16" Stem 25/32" Head Dia.	28668 5/16" x 3/4" Stem 1 21/32" Head Dia.

335 Pcs.

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

CLEANING PRODUCTS

IMMACULATE

GLASS CLEANER & WINDSHIELD WASHER SOLVENT

IMMACULATE may be used as dilutable cleaner for maintenance of all glass surface areas, inside and outside. Also may be used effectively as a windshield washer solvent down to 32°F.

- Cleans and brightens glass without streaking
- Economical, dilutes with up to 10 parts of water
- Ammonia free formula safe for tinted windows, all glass surfaces, chrome, porcelain and formica

APPLICATIONS

Windows	Mirrors
Porcelain	Showcases
Formica	Chrome

Part No.	Description
9686	Case of 4 (1 Gallon Containers)



GLASS CLEANER

- Professional strength glass cleaner breaks through tough grime and residue and polishes to an amazing streak free shine
- Does not contain harsh chemicals like butyl or ammonia, non-flammable
- Foaming action stays where it is sprayed for increased cleaning contact and better coverage
- Fresh fragrance is pleasant to work with
- Safe 100% biodegradable formula
- 20 fl. oz. , 19 oz. net weight



Part No.	Description
8250	Case of 12 Aerosol Cans
8260	1/2 Case of 6 Aerosol Cans

BLUE WIZARD SQUEEGEE

- The fastest way to dry vehicles and windows or to remove standing water
- Unique "T" edge design for superior performance
- Works like a snow broom to push or pull the snow off a vehicle
- Flexible, 2.5" x 12" silicone blade will not scratch painted surfaces
- Threaded, extension pole adjusts from 2 feet to 4 1/2 feet to clean hard-to-reach windows and surfaces
- Threaded to accept standard extension poles
- Kit comes with handle and 16" x 24" microfiber towel



21098

Part No.	Description
21098	Blue Wizard Kit



Unique "T"
Wedge Design

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

TIFCO DAZZLE

TRUCK WASH CONCENTRATE

TIFCO DAZZLE is an advanced premium heavy duty liquid truck wash that is formulated to rapidly remove grease, grime, bugs and tenacious road film from trucks, trailers and other painted vehicles, using little to no agitation, leaving surfaces free of streaks and water spots. This powerful formulation may be applied with pressure washers, steam cleaners, hand washing or automated systems.

- Removes road film streak free,
- Cleans with or without brushing
- Biodegradable, rinses freely
- Contains no acids, phosphates or petroleum solvents
- Concentrated formula for tough jobs on trucks, buses, trailers and heavy equipment
- Works with hot or cold, hard or soft water
- Use with pressure washers, hard washing, steam cleaners, or automated systems

DILUTION RATIOS
1 to 100 - Light Cleaning
1 to 50 - Normal Cleaning
1 to 25 - Heavy Road Film
1 to 5 - Engine Degreasing

Part No.	Description
9718	5 Gallon Container



AUTO-BRIGHT®

LIQUID CAR WASH CONCENTRATE

AUTO-BRIGHT® is a specially designed concentrated cleaner for use in pressure cleaning fleet operations. This cleaner may be diluted with up to 20 parts of water. It quickly and easily removes dirt, grease, bugs and road film from cars, trucks, buses and farm equipment.

- Safe on waxed surfaces
- Goes into solution immediately
- Penetrates dirt and grease quickly
- Leaves no film
- Removes bugs and road film
- Economical - may be diluted with up to 20 parts of water



Part No.	Description
9715	5 Gallon Container




FLEET SPECIALS

AUTOMOTIVE CHEMICALS

FUEL STABILIZER FILTER

WATER REMOVER

- Removes water and contaminants that cause difficulty starting and rough running engines
- Suitable for all 2 and 4 cycle engines in lawn equipment, recreational vehicles, cars and trucks, generators, boats
- Easy, convenient, continuous multi-year protection
- Protects in storage and during operation
- Stabilizes gasoline from 6 months in commercial environments to 2 years in storage
- Non-chemical, non-liquid fuel stabilizer
- Environmentally and eco-friendly
- Includes tethers and clips for easy retrieval
- Removes water bound to ethanol, stopping corrosion and eliminating phase separation



22941



22943

Part No.	Description
22941	Pack of 5 - 20 gram Filters
22943	Individual - 100 gram Filter

FUEL STABILIZER

Use in any gasoline-powered vehicle or equipment you plan to store for 30-days or longer. It keeps the fuel fresh for up to 12 months during storage, eliminating the need to drain your tank. Works effectively in all gasoline blends, including Ethanol-blended fuel, up to E-85. Perfect for collector cars, generators, lawn mowers, snow blowers, etc.



- Keeps fuel fresh for up to 12 months during storage
- Eliminates the need to drain fuel prior to storage
- Ensures quick, easy starts after storage
- Prevents gum and varnish build-up
- Effective in all gasoline, including Ethanol blends
- For all gasoline engines, including 2-cycle



Part No.	Description
7859	Case of 12 (16 oz. Bottles)

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

PLASTIC FUEL TANK REPAIR ADHESIVE

- Fast Drying Time – set in 2-3 minutes
- Gas and oil resistant
- Bond remains secure even when exposed to water
- Abrasion resistant
- Remains tough even in extreme conditions



Part No.	Description
7855	Case of 6 (2 oz. Tubes)

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

HEADLIGHT LENS RESTORER

- For use on headlights, taillight, fog and directional lights to restore "like new" clarity
- Restores clouded, yellowed lens surfaces
- Wipe on - wipe off, no special tools needed
- Eliminates repair/replacement cost



Part No.	Description
9363	Case of 6 (8 oz. Bottles)

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

WINDSHIELD REPAIR KIT

The easy to use Windshield Saver II repairs most typical chip damages using a faster working single part UV resin requiring outdoor sunlight to harden. The resin injection repair process strengthens the weak spot in the windshield by filling the damaged cavity and bonding the loose glass. It also reduces the visual distortion to a slight mark and smooths out the surface, preventing wiper blade streaking.



Part No.	Description
9371	Windshield Repair Kit

PLASTIC WELD KIT

- 1 oz. high strength adhesive
- Easy to use
- Supplied as a kit with an activator
- Full cure in 10-30 seconds
- Capable of penetrating between parts



Part No.	Description
7793	Plastic Weld Adhesive Kit

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

SUPER WEATHERSTRIP AND EMBLEM ADHESIVE

- Fast-setting, high-strength, multi-purpose adhesive for bonding all types of rubber weatherstrip, gaskets, vinyls, emblems, and other trim pieces
- Excellent adhesive for vinyl, metal, fabrics, rubber, paper, and cork gaskets
- Resists oil, grease, solvents, heat, cold and moisture resistant
- Remains flexible and strong, will not become brittle
- Dries clear



Part No.	Description
9579	Emblem Adhesive


AUTOMOTIVE CHEMICALS

TIFCO ARMOR-KOTE

AEROSOL CLEANER/PROTECTIVE COATING

- Cleans and shines in one step
- Silicone-free, non-flammable
- Powerful deodorizer refreshes the surface, removes odors, leaves a pleasant fragrance
- Does not leave a greasy film that can attract dirt and dust
- Contains UV guard, static guard
- 20 fl. oz., 18 oz. net wt.

Note: This product is not intended for use on glass or mirrors.



Part No.	Description
7603	Case of 12 Aerosol Cans
9903	1/2 Case of 6 Aerosol Cans
8022	Individual Can

ARMOR-KOTE™

MULTI-PURPOSE POLISH/PROTECTIVE COATING

ARMOR-KOTE is a unique product that is specially formulated to clean and shine a wide variety of surfaces in one easy operation. It sprays out in fast breaking white foam and easily wipes off with minimal effort to remove dirt and deposits. The special silicone-free formula polishes and shines without leaving a greasy film to attract dust and deposits or fingerprints. Pleasant fragrance, deodorizes, cleans and shines.

- Use on vinyl, rubber, leather, wood and plastics
- Pleasant fragrance
- Non-flammable, non-toxic, non-yellowing, non-corrosive and odorless
- Contains no silicone
- Makes surfaces anti-static to repel dust and dirt
- Protects against ultraviolet rays
- Can be used on interior or exterior surfaces
- Weather resistant - preserves, protects and beautifies



Part No.	Size
9660	Case of 12 Quarts
9669	1/2 Case of 6 Quarts

MAXXKOTE® GRAVEL GUARD – BLACK

- Highest chip resistance
- Use on rocker panels, headers etc.
- Can be sprayed to match OEM finish
- Paintable, fast dry and may be used under all paints
- 20 fl. oz., 16.25 oz. net wt.



Part No.	Description
7782	Case of 12 (20 fl. oz. Aerosol Cans)
7783	1/2 Case of 6 (20 fl. oz. Aerosol Cans)
8302	Individual Can

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

TIFCO RESTORE

RUBBER PARTS REJUVENATOR

RESTORE reverses unsightly damage, quickly and easily, restoring rubber to like new showroom appearance. Oxidized tires and side molding instantly regain their rich black look. Hardened seals and hoses become pliable again stopping leaks. Rejuvenated rubber parts no longer stick and freeze.

- Silicone-free formula is body shop safe and harmless to printed surfaces
- Labor-saving, no wiping required
- Brilliant, "like-new" showroom shine
- 20 fl. oz., 12.25 oz. net wt.



Part No.	Description
7615	Case of 12 Aerosol Cans
9930	1/2 Case of 6 Aerosol Cans
8032	Individual Can

TIFCO FLEXI SEAL®

RUBBERIZED COATING & SOUND DEADENER

TIFCO FLEXI SEAL® is an excellent corrosion proofer that seals out water, dust, and road chemicals. Use FLEXI SEAL™ as an undercoating, or on machinery, equipment, tanks, valves and more as a waterproof coating, caulk and sealant

- Special formula dries quickly yet remains flexible even in cold weather
- Will not peel or crack
- Will not bleed through paint
- Adheres to most hard surfaces
- Sealing ability makes ideal caulk for many small jobs
- Muffles road noises
- 20 fl. oz., 18 oz. net. wt.

Part No.	Description
8188	Case of 12 Aerosol Cans
9928	1/2 Case of 6 Aerosol Cans
8401	Individual Can

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov



TIFCO GRIP-N-KLEEN™

HEAVY DUTY ENGINE DEGREASER

TIFCO GRIP-N-KLEEN™ formulated to remove dirt, oil and heavy buildup from all types of engines. Does not contain chlorinated Fast acting and easy rinsing for a clean bright surface.

- Removes grease, grime, oils and tar
- Superior degreasing ability
- Non-chlorinated
- Rinses clean with water
- Expands and cleans tight areas
- 20 fl. oz., 17 oz. net wt.

Part No.	Description
8180	Case of 12 Aerosol Cans
9926	1/2 Case of 6 Aerosol Cans
8413	Individual Can

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov



FLEET SPECIALS

LITHIUM JUMP STARTER

Jump starts most gas and deisel engines using a 30,000 mAh high capacity, high power battery that is fast charging and has low self-discharge.

- 12V vehicle jump-start, back up charger for all brands of cellphones, notebooks, tablets and other portable electronics
- Powerful, high capacity Nano Lithium battery
- Fast charging with low self-discharge cycle
- Up to 1500 charging cycles
- 800 cranking amps and 1800 peak amps
- Three lighting modes: standard, strobe and SOS
- Four different types of charging modes: 5V 2A, 5V 1A, 19 V 3.5 A, 12V 10 A
- Built in safety protection for jump starter overcharging and over discharging
- Kit includes Intelli-Clamps for jump starting with built-in safety and diagnostic features and multiple charging cables stored in a zippered nylon carry case



Part No.	Rating
45007	30,000 mAh

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

SAFETY CANS

TYPE II SAFETY CANS

- Durable 6-Layer high density polyethylene design with stainless steel springs, aluminum rivets, and viton seals eliminates permeation and improves durability
- Meets all certifications: OSHA, MSHA, DOT, UN, CARB, EPA, FM Approved
- Comfortable grip with safety thumb trigger
- Self venting enables smooth flow without glugging
- Flexible rotating spout rotates over 180° to fit easily into machines fill area
- Flame mitigation device in the fill area prevents sparks from entering can



12706



12712

Part No.	Fuel	Gallons
12706	Gasoline	2(+)
12707	Gasoline	5
12712	Diesel	5

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

SCRUBBLADE

- Double blade design provides excellent all-weather performance by scrubbing and wiping simultaneously
- Patented scrubber design removes bugs, dirt and road debris from your windshield for a clear safe view
- Includes a universal adapter that fits most vehicles
- All season performance and fast, easy installation
- Highest laboratory rated blade available, even after 500,000 cycles
- Reduces driver fatigue by eliminating glare from a dirty windshield




Outer Side

Triangular scrubbers for bug, dirt and road debris removal

Inner Side

Clears off loosened debris and water



Part No.	Size
28905	16"
28907	18"
28909	20"
28910	21"
28911	22"
28912	24"
28913	26"



Eliminate



Annihilate



Obliterate



Remediate

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

VEHICLE SPILL KITS

- Designed to fit under or behind drivers seat, assures local and state law compliance
- Packaged in an anti-static, plastic reclosable bag, kit contains 2 absorbent socks, 20 pads, and bag
- Contains all necessary items to handle one large spill or several small spills, portable and economical



9688



9678

Part No.	Description
9678	Universal Spill Kit
9688	Oil Only Spill Kit

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov



tifco industries
THE RIGHT PART IN THE RIGHT PLACE AT THE RIGHT TIME

tifco.com

Phone: 800.868.4326
Fax: 800.535.4619
tifco@tifco.com

Main Office: Houston, TX
Branch Office: Reno, NV



tifco industries

THE RIGHT PART, IN THE RIGHT PLACE, AT THE RIGHT TIME



AF# 191628
01/12/2024 v17

Main Office: Houston, Texas • Branch Office: Reno, Nevada • Phone: 800.868.4326 • Fax: 800.535.4619 • Website: tifco.com

©REPRODUCTION, IN WHOLE OR IN PART, PROHIBITED